

WOLFF WK91 SL

962-4-004686

Technische Daten

1

Traglasten (kg)		DIN 15018 / H1 - B3			
2 - facher Seilstrangbetrieb mit Unterflasche U6/3					
Ausladung (m)	Auslegerlänge (m)				
	30	36	42	46	50
14,0	3000	3000	3000	3000	3000
15,0	3000	3000	3000	3000	3000
16,0	3000	3000	3000	3000	3000
17,0	3000	3000	3000	3000	3000
18,0	3000	3000	3000	3000	3000
19,0	3000	3000	3000	3000	3000
20,0	3000	3000	3000	3000	3000
21,0	3000	3000	3000	3000	3000
22,0	3000	3000	3000	3000	3000
23,0	3000	3000	3000	3000	3000
24,0	3000	3000	3000	3000	3000
25,0	3000	3000	3000	3000	3000
26,0	3000	3000	3000	3000	3000
27,0	3000	3000	3000	3000	3000
28,0	3000	3000	3000	3000	3000
29,0	3000	3000	3000	3000	3000
30,0	3000	3000	3000	3000	2900
31,0		3000	3000	2900	2790
32,0		3000	3000	2800	2700
33,0		3000	2900	2700	2600
34,0		2850	2750	2590	2485
35,0		2750	2650	2500	2400
36,0		2660	2600	2400	2300
37,0			2480	2330	2230
38,0			2400	2255	2160
39,0			2320	2180	2090
40,0			2250	2110	2020
41,0			2180	2050	1960
42,0			2110	2000	1900
43,0				1920	1840
44,0				1870	1780
45,0				1810	1730
46,0				1760	1700
47,0					1630
48,0					1590
49,0					1540
50,0					1500

WOLFF WK91 SL

962-4-004687

Technische Daten

1

Traglasten (kg)		DIN 15018 / H1 - B3			
4 - facher Seilstrangbetrieb mit Unterflasche U6/3					
Ausladung (m)	Auslegerlänge (m)				
	30	36	42	46	50
14,0	6000	6000	6000	6000	6000
15,0	6000	6000	6000	6000	6000
16,0	6000	6000	6000	6000	6000
17,0	6000	6000	6000	5890	5670
18,0	6000	6000	5820	5515	5310
19,0	6000	5660	5470	5180	4980
20,0	5800	5300	5200	4900	4700
21,0	5450	5040	4870	4610	4440
22,0	5170	4780	4620	4370	4200
23,0	4910	4540	4380	4150	3990
24,0	4670	4320	4170	3950	3790
25,0	4500	4100	4000	3800	3600
26,0	4260	3930	3800	3590	3450
27,0	4075	3760	3630	3430	3290
28,0	3905	3600	3480	3285	3150
29,0	3700	3500	3300	3100	3000
30,0	3600	3300	3200	3000	2900
31,0		3190	3080	2900	2790
32,0		3100	3000	2800	2700
33,0		3000	2900	2700	2600
34,0		2850	2750	2590	2485
35,0		2750	2650	2500	2400
36,0		2660	2600	2400	2300
37,0			2480	2330	2230
38,0			2400	2255	2160
39,0			2320	2180	2090
40,0			2250	2110	2020
41,0			2180	2050	1960
42,0			2110	2000	1900
43,0				1920	1840
44,0				1870	1780
45,0				1810	1730
46,0				1760	1700
47,0					1630
48,0					1590
49,0					1540
50,0					1500

WOLFF WK91 SL

962-4-004708

Technische Daten

1

Traglasten (kg)		DIN 15018 / H1 - B3			
2 - facher Seilstrangbetrieb mit Unterflasche U3					
Ausladung (m)	Auslegerlänge (m)				
	30	36	42	46	50
14,0	3000	3000	3000	3000	3000
15,0	3000	3000	3000	3000	3000
16,0	3000	3000	3000	3000	3000
17,0	3000	3000	3000	3000	3000
18,0	3000	3000	3000	3000	3000
19,0	3000	3000	3000	3000	3000
20,0	3000	3000	3000	3000	3000
21,0	3000	3000	3000	3000	3000
22,0	3000	3000	3000	3000	3000
23,0	3000	3000	3000	3000	3000
24,0	3000	3000	3000	3000	3000
25,0	3000	3000	3000	3000	3000
26,0	3000	3000	3000	3000	3000
27,0	3000	3000	3000	3000	3000
28,0	3000	3000	3000	3000	3000
29,0	3000	3000	3000	3000	3000
30,0	3000	3000	3000	3000	3000
31,0		3000	3000	3000	2930
32,0		3000	3000	2900	2800
33,0		3000	2900	2800	2700
34,0		2990	2890	2730	2625
35,0		2890	2790	2640	2540
36,0		2800	2700	2600	2500
37,0			2620	2470	2370
38,0			2540	2395	2300
39,0			2460	2320	2230
40,0			2385	2250	2160
41,0			2320	2190	2100
42,0			2250	2100	2000
43,0				2060	1980
44,0				2010	1920
45,0				1950	1870
46,0				1900	1800
47,0					1770
48,0					1730
49,0					1680
50,0					1640